

# SOLIDAL® CMC Double Folded System

<b>Model</b>	<b>SOLIDAL® CMC (Custom Modular Cassette) Double Folded System</b>
<b>Thickness</b>	T2® (2mm), T3® (3mm), T4® (4mm)
<b>Corners</b>	Smartwelded®
<b>Module Stiffeners</b>	Mechanically Fixed
<b>Joint Type</b>	Dry Joint (Rainscreen)
<b>Finish</b>	Powder Coat (Akzonobel Interpon / Dulux Duratec) or PVDF Wet Spray (P.P.G) in unlimited colours, single side or double side coating. Anodise Finish.

**Protect your Spec. & your Environment** Recommended comments for architectural specification:  
**SOLIDAL® Post Applied Paint, Mechanically Fixed Stiffeners, Smartwelded Corners.**  
**100% Recyclable (No combustible Glues or Tapes used)**

Max Width	Up to 2000mm* (Custom)
Max Length	Up to 5960mm* (Custom)
Joint Width	12-15mm (Custom)
Joint Depth	Up to 90mm* (Standard 25mm)
Folds	Sharp Edge or Rounded Edge
Weight	T2® 5.4kg/m <sup>2</sup> (2mm), T3® 8.1kg/m <sup>2</sup> (3mm), T4® 10.4kg/m <sup>2</sup> (4mm)

#### Applications:

Cladding | Facades | Roofing | Soffit | All Building Envelopes

#### Attachment Methods:

Screw Fixed through perimeter SOLIDAL® Folded Flange into Subframe. Optional Cleat System.



**NATA Certified AS1530.1 & AS1530.3**